

Diver Down™ Custom Neoprene Seat Covers

Installation Manual: for 1997- Current Jeep Wrangler Vehicles
#14167.20XX



PARTS LIST:

Front Seat Cover Set
Rear Seat Cover Set

REQUIRED TOOLS:

No tools required.

⚠ CAUTION ⚠

READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING TO INSTALL THIS PRODUCT. ALWAYS WEAR SAFETY GLASSES DURING INSTALL.



The Trusted Source

A Few Words About Product Safety:

Your Diver Down™ seat covers are intended to protect your seats and enhance the comfort and style of your vehicle interior. Before installation, please take a moment to review the following safety information and installation instructions. Important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words mean:

⚠ WARNING ⚠

A hazardous situation which, if not avoided, could result in death or serious injury. You **CAN** be **KILLED** or **SERIOUSLY HURT** if you don't follow instructions.

⚠ CAUTION ⚠

A hazardous situation which, if not avoided, could result in minor or moderate injury. You **CAN** be moderately **HURT** and also may suffer property damage if you don't follow instructions.

NOTICE

Careful attention is required to this instruction or operation but does generally not relate to personal injury. Damage to your Quadratrac® product or other property may result if you don't follow instructions.

Seat Covers Installation:

Prepare your seat covers for installation. Make sure to unbuckle all straps and unzip all zippers on your seat covers prior to installation.

For JK only:

Remove front headrests by depressing the release tabs at the base of the headrest posts and lift up on headrest.

Front seat covers are designed specifically for the passenger or driver sides of the vehicle and are not interchangeable.

⚠ WARNING ⚠

(JK ONLY) IF YOUR VEHICLE IS EQUIPPED WITH SIDE IMPACT AIRBAGS MAKE SURE THAT YOU POSITION THE AIRBAG FLAPS OVER THE AIRBAGS, ON THE OUTSIDE OF THE SEAT FACING THE DOORS. FAILURE TO DO SO COULD LESSEN THE EFFECTIVENESS OF THE AIRBAGS.

Start by slipping the seat cover over the back of your vehicle's seat and pulling it down all the way over seatback. For JK vehicles, ensure that the holes for the headrest on the covers line-up with the holes in the seat.

Tuck the connecting flap or straps of the seat cover between the seat base and seat-back. Folding the seat forward may make this process easier. Zip all zippers on the seat cover. On two-piece covers, attach the connecting flap with the hook and loop fasteners on the back of the seat cover.

On two-piece seat covers install the seat bottom cover over the seat base and pass the connection flap and straps between the seatback and seat base. On one-piece covers, make sure the buckles and straps are tucked all the way through the crevice between the seatback and base.



The Trusted Source

Seat Covers Installation: continued

Underneath the seat, connect and tighten the buckles and straps from the back of the seat cover with the buckles at the front of the seat cover.

NOTICE

USE THE STRAPS FOR FINAL ADJUSTMENT ONLY. DO NOT PULL TOO HARD OR OVER-TIGHTEN THE STRAPS. THIS COULD CAUSE DAMAGE TO THE SEAT COVERS.

Pull the sides of the seat cover all the way down over the sides of the seat base. Attach the elastic straps with hooks to the buckled straps under the seats or to part of the underside of the seat base.

⚠ CAUTION ⚠

DO NOT ATTACH STRAPS OR HOOKS TO ANY PART OF THE SEAT THAT MIGHT IMPEDE PROPER OPERATION OF THE SEAT.

For JK vehicles only:

Install headrest covers and reinstall headrests.

Finish installation by adjusting the seat covers around and behind all seat levers, adjusters, covers, and trim.

⚠ CAUTION ⚠

BEFORE DRIVING, TEST THE OPERATION OF THE SEATS. IF THE SEAT OPERATION IS IMPAIRED BY THE COVER, MAKE ADJUSTMENTS TO THE INSTALLATION OF THE SEAT COVER, AND TEST THE OPERATION OF THE SEAT AGAIN. DO NOT DRIVE THE VEHICLE UNLESS THE SEATS OPERATE PROPERLY.

Care of your product:

Periodic adjustments to the seat covers may be necessary as the cover breaks in and conforms to your vehicle's seat. Seat covers can be spot cleaned with mild soap and water and a soft bristle brush. Do not machine wash.

Sunlight will naturally fade neoprene over time.

Seat covers are warrantied against defects in workmanship and materials, but not for fading due to normal UV exposure. See p4 for complete warranty information.

For Further Information:

A Quadratec seat cover installation video is available @ www.quadratec.com



The Trusted Source