



## Custom Neoprene Seat Covers

**Installation Manual: for 2018-Current Jeep Wrangler JL Vehicles**  
#14167.40XX



**PARTS LIST:**

Front Seat Cover Set  
Rear Seat Cover Set

**REQUIRED TOOLS:**

No tools required.



**READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING TO INSTALL THIS PRODUCT. ALWAYS WEAR SAFETY GLASSES DURING INSTALL.**

### **A Few Words About Product Safety:**

Your Diver Down® seat covers are intended to protect your seats and enhance the comfort and style of your vehicle's interior. Before installation, please take a moment to review the following safety information and installation instructions. Important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words mean:

#### **⚠ WARNING ⚠**

A hazardous situation which, if not avoided, could result in death or serious injury. You **CAN** be **KILLED** or **SERIOUSLY HURT** if you don't follow instructions.

#### **⚠ CAUTION ⚠**

A hazardous situation which, if not avoided, could result in minor or moderate injury. You **CAN** be moderately **HURT** and also may suffer property damage if you don't follow instructions.

#### **NOTICE**

Careful attention is required to this instruction or operation but does generally not relate to personal injury. Damage to your product or other property may result if you don't follow instructions.

### **Seat Covers Installation:**

Prepare your seat covers for installation. Make sure to unbuckle all straps and unzip all zippers on your seat covers prior to installation.

Remove front headrests by depressing the release tabs at the base of the headrest posts and lift up on headrest.



Front seat covers are designed specifically for the passenger and driver side of the vehicle and are not interchangeable. The Diver Down sew bar tags on front seats always face to the center of the vehicle.

#### **⚠ WARNING ⚠**

**YOUR VEHICLE IS EQUIPPED WITH SIDE IMPACT AIRBAGS. MAKE SURE THAT YOU INSTALL THE CORRECT SEAT COVERS FOR YOUR YEAR AND MODEL. ALSO ENSURE THAT PASSENGER AND DRIVER SIDE SEAT COVERS ARE INSTALLED ON THE CORRECT SEAT. FAILURE TO DO SO COULD LESSEN THE EFFECTIVENESS OF THE AIRBAGS.**

Start by slipping the seat cover over the back of your vehicle's seat and pulling it down all the way over seatback. Ensure that the holes for the headrest in the covers line up with the grommets in the seat.

Tuck the connecting flaps of the seat cover between the seat base and seat back. Folding the seat forward may make this process easier. Zip up all zippers on the seat cover (if applicable). Attach the connecting flaps with the hook and loop fasteners on the back of the seat cover.

Install the seat bottom cover over the seat base and pass the connecting straps between the seat back and seat base. Make sure the buckles and straps are tucked all the way through the crevice between the seat back and base.

### Seat Covers Installation: continued

*Underneath the seat, connect and tighten the buckles and straps from the back of the seat cover with the buckles at the front of the seat cover.*

#### **NOTICE**

**USE THE STRAPS FOR THE FINAL ADJUSTMENT ONLY. DO NOT PULL TOO HARD OR OVER TIGHTEN THE STRAPS. THIS COULD CAUSE DAMAGE TO THE SEAT COVERS.**

*Pull the sides of the seat cover all the way down over the sides of the seat base. Attach the elastic straps with hooks to the buckled straps under the seats or to part of the underside of the seat base.*

#### **⚠ CAUTION ⚠**

**DO NOT ATTACH STRAPS OR HOOKS TO ANY PART OF THE SEAT THAT MIGHT IMPEDE OPERATION OF THE SEAT.**

*Finish installation by adjusting the seat covers around and behind all seat levers, adjusters, covers, and trim.*



*Seat covers can be carefully tucked under and around the headrest grommets. This will provide a more finished look and retain access to headrest release tabs.*



*Finally, Install headrest covers and reinstall headrests.*

#### **Product Care:**

*Periodic adjustments to the seat covers may be necessary as the covers break-in and conform to your vehicle's seat. Seat covers can be spot cleaned with mild soap and water and a soft bristle brush. Do not machine wash.*

#### **Sunlight will naturally fade neoprene over time.**

*Seat covers are warrantied against defects in workmanship and materials, but not for fading due to normal UV exposure. See next page for complete warranty information.*

#### **⚠ CAUTION ⚠**

**BEFORE DRIVING, TEST THE OPERATION OF THE SEATS. IF THE SEAT OPERATION IS IMPAIRED BY THE COVER, MAKE ADJUSTMENTS TO THE INSTALLATION OF THE SEAT COVER, AND TEST THE OPERATION OF THE SEAT AGAIN. DO NOT DRIVE THE VEHICLE UNLESS THE SEATS OPERATE PROPERLY.**

#### **Further Information:**

*A Quadratic seat cover installation video is available @ [www.quadratec.com](http://www.quadratec.com)*