



## Installation Instructions Targa/Safari Style Sun Bikini Top

Vehicle Application:  
Jeep® Wrangler Unlimited JL 2018-Current  
Part Number 52410 - 52411 - 52412

### Installation Tips

Before you begin installing your new Sun Bikini Top, please read all the instructions thoroughly.



#### WARNING

Do not rely in any way on the components of this product to protect against injury or death in the event of an accident. Never operate the vehicle in excess of manufacturer's specifications.

Read and follow, precisely, all installation instructions provided when installing this product. Failure to do so may result in a poor fit and could place occupants of the vehicle in a potentially dangerous situation.



### WEAR SEAT BELTS AT ALL TIMES



#### CAUTION

Safety glasses should be worn at all times when installing this product.

### Tools



Safety Glasses



T25 - Torx Driver



Phillips Screwdriver

### Installation Time



30 minutes

### Skill Level



1 - Easy

### Support

We're here to help! Go to:  
<https://www.bestop.com>  
and click on **Need Help?**



<https://www.bestop.com/video-library>



## Installation Instructions Targa/Safari Style Sun Bikini Top

Vehicle Application:  
Jeep® Wrangler Unlimited JL 2018-Current  
Part Number 52410 - 52411 - 52412

### Sugerencias de Instalación

**Antes de empezar a instalar esta unidad, lea atentamente todas las instrucciones.**

**Para un buen ajuste:**

Para facilitar la instalación, el producto debe instalarse a temperaturas superiores a 72 °F (22 °C).

Por debajo de esta temperatura, la tela puede encogerse una pulgada o más, lo que dificultaría su ajuste al vehículo.

Es normal que la tela se contraiga o arrugue cuando está guardada en la caja de empaque. A los pocos días después de la instalación, la tela se relajará y las arrugas desaparecerán.



#### ADVERTENCIA

Este producto se diseñó principalmente para mejorar la apariencia del vehículo y proteger a los ocupantes de las condiciones climáticas comunes. De ninguna manera piense que los componentes de este producto pueden servir como medio de contención para los ocupantes del vehículo o que pueden protegerlos contra lesiones o la muerte en caso de accidente. Este producto no protegerá a los ocupantes contra caídas de objetos. Nunca conduzca este vehículo fuera de las especificaciones del fabricante.

#### USE LOS CINTURONES DE SEGURIDAD EN TODO MOMENTO

Lea y siga con precisión todas las instrucciones de instalación que se proporcionan para instalar este producto. Si no lo hace, podría producirse un mal ajuste que colocaría a los ocupantes del vehículo en una situación potencialmente peligrosa.



#### PRECAUCIÓN

Debe usar gafas protectoras en todo momento durante la instalación de este producto.

### Conseils pour l'installation

**Lire toutes les instructions au complet avant de commencer l'installation de cet assemblage.**

**Pour un ajustement sans problème :**

Afin de faciliter l'installation, ce produit doit être installé à des températures au-dessus de 72 °F (22 °C).

Sous cette température, le tissu peut rétrécir d'un pouce (2,5 cm) ou plus, ce qui rendra l'ajustement sur le véhicule difficile.

Il est normal que le tissu rétrécisse et plisse pendant qu'il est dans la boîte d'expédition. En quelques jours après l'installation, le tissu se détendra et les plis disparaîtront.



#### AVERTISSEMENT

Ce produit est conçu principalement pour améliorer l'apparence du véhicule et pour protéger les occupants des conditions météorologiques usuelles. Ne jamais se fier aux composants de ce produit pour se protéger de blessures ou de la mort en cas d'accident. Ce produit ne protégera pas les occupants des chutes d'objets. Ne jamais utiliser le véhicule au-delà des caractéristiques techniques indiquées par le fabricant.

#### PORTER UNE CEINTURE DE SÉCURITÉ EN TOUT TEMPS

Lire et suivre, très fidèlement, toutes les instructions d'installation fournies lors de l'installation de ce produit. Ne pas suivre cette consigne peut causer une installation inadéquate et mettre les occupants du véhicule dans une situation potentiellement dangereuse.



#### MISE EN GARDE

Des lunettes de sécurité doivent être portées en tout temps lors de l'installation de ce produit.








## Installation Instructions Targa/Safari Style Sun Bikini Top

Vehicle Application:  
Jeep® Wrangler Unlimited JL 2018-Current  
Part Number 52410 - 52411 - 52412



### Parts List

- Required parts for installation      - Page number in Installation Guide

Sections 2 & 3      Snap Stud Screws, Snap Straps		Pages 7 to 9 of Guide
 <p>Snap Stud Screw #8x5/8" Part #728221 Qty. 10</p>	 <p>Snap Straps Varying Lengths Qty. 10</p>	 <p>Tail Clip Part #338.24 Qty. 10</p>
Sections 4 to 6      Targa/Safari Style Sun Bikini Top		Pages 10 to 13 of Guide
 <p>Safari Style Sun Bikini Top Size will vary depending on application Qty. 1</p>	- OR -	 <p>Targa Style Sun Bikini Top Qty. 1</p>

**Step 1****Tools**

T25 - Torx Driver

**Step 2****Step 1**

Safari and Targa Tops:

Remove two Torx screws from the underside of the sport bar over the front doors in the locations shown.


Left (driver) side shown. Remove these two screws on both sides of the Jeep.

**Step 2**

Safari Top Only:



Remove two Torx screws from the underside of the sport bar over the rear doors in the locations shown.

Left (driver) side shown. Remove these two screws on both sides of the Jeep.



**Step 1****Tools**

T25 - Torx Driver

**Step 2****Step 1**

Safari and Targa Tops:

Remove two Torx screws from the underside of the sport bar over the front doors in the locations shown.

Left (driver) side shown. Remove these two screws on both sides of the Jeep.

**Step 2**

Safari Top Only:

Remove two Torx screws from the underside of the sport bar over the rear doors in the locations shown.

Left (driver) side shown. Remove these two screws on both sides of the Jeep.




## 4-Door

## Tools



T25 - Torx Driver


## 2-Door



## Step 3

4-Door Jeeps:

Remove the Torx screw on the inside-facing side of each sport bar down-tube.



## Step 3

2-Door Jeeps:

Remove the Torx screw on the front-facing side of each sport bar down-tube.




## Step 1 728221

## Hardware




Snap Stud Screw  
#8x5/8"  
Part #728221  
Qty. 10

## Tools



Phillips Screwdriver




## Step 1

Safari Tops:

In all ten (10) locations that you removed the Torx screws from the sport bar, on both sides of the Jeep, install Snap Stud Screws.



Targa Tops:

In all four (4) locations that you removed the Torx screws from the sport bar, on both sides of the Jeep, install Snap Stud Screws.




Safari Top Only



**Step 1****Hardware**

Snap Straps  
Front - Short Straps  
Rear - Longer Straps  
Qty. 4 of each

**Step 1**

Attach the shorter Snap Straps to the Snap Studs in the four (4) front sport bar locations - two on each side of the Jeep.

Straps should be positioned so that the straps hang to the outside of the Jeep.

Attach the longer Snap Straps to the Snap Studs in the four (4) rear sport bar locations - two on each side of the Jeep. (Safari Top Only)

Straps should be positioned so that the straps hang to the outside of the Jeep.








4-door

Hardware

2-door


**Step 1**

Attach the longer Snap Straps to the Snap Studs in the two (2) sport bar down-tube locations - one on each side of the Jeep.


Note the different locations where you replaced the Torx screws with Snap Stud Screws on the 4-door or 2-door Jeep.



## Step 1




## Hardware



Safari-Style Sun Bikini

Targa-Style Sun Bikini



## Step 1


Lay the Sun Bikini on top of the Jeep, with the magnets at the front, and the long corner straps at the rear.

Place the Bikini so that the magnets come into contact with the metal part of the windshield header that is the same height as the top of the sport bar.



**Step 1****Hardware**

Tail Clip  
Part #338.24  
Qty. 10



**Step 1**

Attach the straps to the buckles loosely in the order shown, 1 to 10.

Snug the straps 1 and 2, then wrap the long straps at the rear around the sport bar at the rear as shown, and attach to the corner buckles. Snug these two straps, 3 and 4.

Now snug the rest of the straps in the order shown, 5 to 10.

Dress the loose ends of the straps with the Tail Clips, #338.24



**Rear Strap**

## Step 1

## Hardware



Tail Clip  
Part #338.24  
Qty. 10




## Step 1


Attach the straps to the buckles loosely in the order shown, 1 to 6.

Snug the straps 1 and 2, then wrap the long straps at the rear around the sport bar and soundbar at the rear as shown, and attach to the corner buckles. Snug these two straps, 3 and 4.

Now snug straps 5 and 6.

Dress the loose ends of the straps with the Tail Clips, #338.24



**Step 1****Step 1**

To open the Freedom Panels, release the four (4 ) magnets at the front of the Top, then unzip the Zippered Center Access, to allow access to the Freedom Panels.