





Soft Tire Cover


www.mopar.com




1. Remove beauty cover (see owner's manual).




2. Insert cover cone onto camera stalk.




3. Work cover from top down, over the tire.



4. Open back door. Work cover until covered.




5. Camera view with and without tire cover.




6. TO REMOVE, work cover from bottom to top. Disengage cone, pull down and remove from stalk.




Housse souple de roue de secours




1. Extraire l'enjoliveur d'embout (voir le manuel d'utilisation).




2. Insérer le cache conique sur l'embout de caméra.




3. Placer la housse sur la roue, de haut en bas.



4. Ouvrir le hayon. Ajuster la housse pour envelopper complètement la roue.



5. Vue de caméra avec et sans housse de roue.




6. POUR L'EXTRAIRE, désinsérer le cache conique de bas en haut. Le tirer vers le bas et l'extraire de l'embout.




Funda para neumáticos


www.mopar.com




1. Retire el embellecedor (consulte el manual del propietario).




2. Inserte el cono protector en la varilla de la cámara.




3. Extienda la funda de arriba abajo, sobre el neumático.



4. Abra la puerta del maletero. Extienda la funda hasta tapar el neumático.



5. Vista de la cámara con y sin funda del neumático.



6. PARA EXTRAERLA, retire la funda de abajo arriba. Desenganche el cono, tire de él hacia abajo y sáquelo de la varilla.